

Redexim



TOP DRESSING



R i n k 1210

The Rink 1210 offers the widest brush applicator top dresser available with a smooth, even spread, over 6 feet (1.80 meters) wide. The four pivoting wheels ensure equal and low ground pressure, even on undulating ground. The full width continuous loopbelt has edge guides to ensure central tracking. The Rink delivery and metering system is designed to ensure smooth, even distribution of all types of top dressing materials, including wet sand.

| FEATURE | BENEFIT |
|---------------------------|--|
| Precise Metering | Enables fine control over density |
| Easy Belt Adjustment | Two tracking guides keep belt centered |
| Exact Spreading Widths | For neat and economical operation |
| Ideal Weight Distribution | Prevents compaction and damage to turf |



TOP DRESSING

Rink 1210



| SPECIFICATIONS | DESCRIPTION |
|---|---|
| Length | 96" (2.40 m) |
| Road Width | 81" (2.03 m) |
| Height | 44" (1.10 m) |
| Loading Capacity | 1.3 cu. yd. (1.0 cu. m.) |
| Spreading Width | 72" (1.80 m) |
| Tire Equipment | 4 Swing tires Trelleborg Garden Slick 18 x 9.50-8 |
| Tire Pressure | 15 psi (1.0 bar) |
| Speed Limit | 19 mph (30 kph) |
| Towing Capacity | minimum 15 hp (20 kw) |
| Spreading Amount | Continuously adjustable |
| Minimum Conveying Capacity Towing Vehicle | 3.6 US gal/min (15 L/min) |
| Hydraulics Required | 3.6 gpm/980 psi |
| Optional | <ul style="list-style-type: none"> - Infill Kit - Hopper extension kit makes the hopper capacity 2 cubic meter for rubber infill only |

